

**Dynamic Engineered Systems, would like to introduce the  
New RER Quick Ship Tower Line  
Units are ready to ship in 30 Days from order.**

**ROS Model**



**RER Model ROS Cooling Towers are all 304 SST Constructed and include:**

- 52 to 236 Nominal Tons
- Factory Certified Performance
- Makeup Water Float and Valve
- Stainless Steel Fan Guard
- PVC Fill and Drift Eliminators and Air Inlet Louver
- Aluminum Alloy Hollow Airfoil Fan
- Ladder and Handrails
- Gravity Spray Distribution with nozzles.

Tons at 3 GPM Per Ton	Condition Reference #	10	11	12	13	14	15
	Wet Bulb °F	68	70	72	74	76	78
	Range °F	10	10	10	10	10	10
	Approach °F	17	15	13	11	9	7
	Inlet Water Temperature °F	95	95	95	95	95	95
	Outlet Water Temperature °F	85	85	85	85	85	85
52	ROS- 711P in GPM	273.3	252.4	230.6	207.5	183.1	157
65	ROS- 711G in GPM	341.6	315.5	288.3	259.3	228.9	196
75	ROS-714D in GPM	391.3	361.4	330.2	297.1	262.2	225
83	ROS-714P in GPM	434.7	401.6	366.9	330.1	291.3	250
104	ROS- 714G in GPM	540.3	499.1	456.0	410.2	362.0	311
82	ROS- 731G in GPM	428.5	395.9	361.6	325.4	287.1	246
142	ROS-734MG in GPM	739.1	682.7	623.7	561.1	495.2	425