



Dynamic Engineered Systems, would like to introduce the New RER Quick Ship Tower Line Units are ready to ship in 30 Days from order.

ROT Model



RER Model ROT Cooling Towers are all 304 SST Constructed and include:

- · 43 to 87 Nominal Tons
- · Factory Certified Performance
- · Makeup Water Float and Valve
- · Stainless Steel Fan Guard
- · PVC Fill and Drift Eliminators and Air Inlet Louver
- · Aluminum Alloy Hollow Airfoil Fan
- · Ladder and Handrails
- · PVC Spray Distribution with nozzles.

Tons at 3 GPM							
Per Ton	Condition Reference #	10	11	12	13	14	15
	Wet Bulb °F	68	70	72	74	76	78
	Range °F	10	10	10	10	10	10
	Approach °F	17	15	13	11	9	7
	Inlet Water Temperature °F	95	95	95	95	95	95
	Outlet Water Temperature °F	85	85	85	85	85	85
43	ROT 911MG in GPM	223.6	206.5	188.7	169.7	149.8	129
87	ROT 941MG in GPM	453.4	418.8	382.6	344.2	303.8	261

Certification of Energy Saving Products

- CTI, Cooling Technology Institute
- CSA, Canadian Stand ards Association
- CWB, Canadian Welding Bureau
- ARI, Air Conditioning and Refrigeration Institute
- =B=R, Institute of Boiler and Radiation Manufacturers 🛕 🔲 🕞
- ISO9001-2008, ISO14001-2004, OHSAS18001-2007











ROT-911



